TK HIRE

Operating and safety instructions for diamond core drill

SAFETY FIRST:

If you are collecting the equipment for someone else please make sure this sheet is given to the equipment user to read. In accordance with Health and Safety in Employment Act requirements, this sheet should be given to the site supervisor if the equipment is being hired for use at a commercial worksite so that the information is available to all users.

Required Safety Equipment



PRE START CHECKS & SAFETY

- ! Ensure the machine has a current Electrical ticket.
- ! Always use machine with two hands
- ! Always use rig
- ! Check that holes to be drilled are clear of pipes and electrical wiring etc.
- ! Be aware that kick back of machine can occur when striking hidden objects.
- ! Ensure the switch is in the off-position before connecting to power source.
- ! Keep proper footing and balance at all times.
- ! Beware of loose clothing and hair.

STARTING PROCEDURE

- ! Squeeze the lockable trigger switch to start the machine. To lock the switch on, press the lock button while holding the rigger switch on, squeeze the trigger and release.
- ! Keep an eye on the indicator light: If flashing between red and green lessen the feed pressure.
- ! When the cut is almost finished, the bit may get stuck. Take extra care gripping the machine tightly and reduce feed pressure.

WHEN OPERATING

- ! Do not force the drill
- ! Disconnect the drill from the power before changing the bit.
- ! Always hold cutter with both hands.
- ! Always use rig supplied.
- ! Choose the slowest speed for large bits and hard materials.
- ! Never change gears when machine is running.